




**STRONG PARTNERS.
TOUGH TRUCKS.™**

J50-60XNL INTEGRATED LITHIUM-ION TECHNICAL GUIDE

WWW.HYSTER.COM

> J50-60XNL DIMENSIONS



J50-60XNL MAST DIMENSIONS

Maximum Fork Height (TOF) in (mm)		Overall Lowered Ht. in (mm)		Overall Extended Height w/ Load Backrest in (mm)		Overall Extended Height w/o Load Backrest in (mm)		Free-Lift (TOF) w/Load Backrest in (mm)		Free-Lift (TOF) w/o Load Backrest in (mm)		Truck Weight lb (kg)	
J50XNL	J60XNL	J50XNL	J60XNL	J50XNL	J60XNL	J50XNL	J60XNL	J50XNL	J60XNL	J50XNL	J60XNL	J50XNL	J60XNL
2-STAGE LIMITED FREE-LIFT (LFL) VISTA MAST													
133 (3392)	126 (3209)	87 (2192)	87 (2192)	182 (4622)	175 (4444)	156 (3956)	152 (3861)	5 (140)	5 (150)	5 (150)	5 (150)	9540 (4330)	10400 (4720)
141 (3592)	134 (3409)	91 (2292)	91 (2292)	190 (4822)	183 (4644)	164 (4156)	160 (4061)	5 (140)	5 (150)	5 (150)	5 (150)	9580 (4350)	10430 (4730)
2-STAGE FULL FREE-LIFT (FFL) VISTA MAST													
133(3402)	126 (3210)	87 (2192)	87 (2192)	183 (4632)	175 (4445)	157 (3966)	152 (3862)	37 (962)	37 (957)	60 (1540)	60 (1540)	9580 (4350)	10430 (4730)
141 (3602)	134 (3410)	91 (2292)	91 (2292)	191 (4832)	183 (4645)	164 (4166)	160 (4062)	41 (1062)	41 (1057)	64 (1640)	64 (1640)	9620 (4365)	10470 (4750)
3-STAGE FULL FREE-LIFT (FFL) VISTA MAST													
183 (4650)	181 (4618)	81 (2042)	85 (2142)	232 (5880)	231 (5853)	205 (5196)	207 (5252)	32 (812)	35 (907)	59 (1508)	59 (1508)	9770 (4435)	10760 (4885)
189 (4800)	187 (4768)	83 (2092)	89 (2242)	238 (6030)	237 (6003)	211 (5346)	213 (5402)	33 (862)	39 (1007)	63 (1608)	63 (1608)	9790 (4445)	10810 (4905)
194 (4950)	193 (4918)	85 (2142)	91 (2292)	244 (6180)	243 (6153)	217 (5496)	219 (5552)	35 (912)	41 (1057)	65 (1658)	65 (1658)	9810 (4455)	10830 (4920)
200 (5100)	205 (5218)	89 (2242)	95 (2392)	250 (6330)	255 (6453)	223 (5646)	231 (5852)	41 (1062)	45 (1157)	69 (1758)	69 (1758)	9850 (4470)	10890 (4945)
206 (5250)	217 (5518)	91 (2292)	101 (2542)	256 (6480)	266 (6753)	229 (5796)	243 (6152)	41 (1112)	51 (1307)	75 (1908)	75 (1908)	9890 (4490)	11070 (5052)
212 (5250)		93 (2342)		261 (6630)		235 (5946)		43 (1112)				9920 (4505)	

J50-60XNL SPECIFICATIONS <

GENERAL	1	Manufacturer		Hyster	Hyster		
	2	Model designation		J50XNL	J60XNL		
	3	Power / voltage		Electric / 80 volts	Electric / 80 volts		
	4	Operation		Sit	Sit		
	5	Rated capacity	lb (kg)	5000 (2268)	6000 (2722)		
	6	Load center	in (mm)	24 (610)	24 (610)		
TIRES	7	Tire type (std / opt)		Pneumatic / pneumatic shaped solid	Pneumatic / pneumatic shaped solid		
	8	Tire size (drive/steer)	in	23x10-12 / 18x7-8	23x10-12 / 18x7-8		
DIMENSIONS	9	Wheels - number X=driven (drive / steer)	front/rear	2X/2	2X/2		
	10	Tread (center of tires) (std dr / wide dr / steer)	in (mm)	36.9 / 41.5 / 39.1 (938 / 1054 / 992)	36.9 / 41.5 / 39.1 (938 / 1054 / 992)		
	11	Mast tilt (std / opt / opt) (forward / rearward)	degrees	5/5 10/5 5/6	5/5 10/5 5/6		
	12	Mast - lowered height (std mast)	in (mm)	87 (2192)	87 (2192)		
	13	Free lift - top of fork	Std 2 std limited free lift mast in (mm)	5 (140)	5 (140)		
		Op 2 stg full free lift mast with / without LBR	in (mm)	37 / 64 (962 / 1628)	37 / 60 (957 / 1540)		
	14	Lift height - top of fork	Std 2 stg limited free lift mast in (mm)	133 (3392)	126 (3209)		
	15	Mast - extended height (std mast with / without LBR)	in (mm)	182 / 156 (4622 / 3956)	175 / 153 (4444 / 3861)		
	16	Overhead guard height	in (mm)	86.3 (2193)	86.3 (2193)		
	17	SIP to bottom of OHG (seat depressed) (std / susp / air ride)	in (mm)	36.9 / 41.5 / 39.1 (938 / 1054 / 992)	36.9 / 41.5 / 39.1 (938 / 1054 / 992)		
	18	Tow pin height (vertical center of pin)	in (mm)	10.3 (262)	10.3 (262)		
	19	Overall width	Pneumatic tires (std / wide tread) in (mm)	46.9 / 51.5 (1192 / 1308)	46.9 / 51.5 (1192 / 1308)		
			PSS tires (std / wide tread) in (mm)	46.2 / 50.7 (1173 / 1289)	46.2 / 50.7 (1173 / 1289)		
	20	Forks (thickness x width x length)	in (mm)	1.6 x 3.9 x 42 (40 x 100 x 1067)	2 x 4.9 x 42 (50 x 125 x 1067)		
	21	Standard carriage width	in (mm)	42 (1067)	42 (1067)		
	22	Ground clearance - lowest point (NL / RL)	in (mm)	3.9 / 3.3 (98 / 83)	3.9 / 3.3 (98 / 83)		
	23	Ground clearance - center of truck (NL / RL)	in (mm)	5.4 / 5.3 (137 / 134)	5.4 / 5.3 (137 / 134)		
	24	Load distance (center of wheel to face of forks)	in (mm)	15.9 (404)	16.4 (416)		
	25	Battery compartment	Height in (mm)	12.6 (320)	12.6 (320)		
			Width in (mm)	29.1 (738)	29.1 (738)		
			Length - nominal Size	34	34		
			Length - actual in (mm)	39.4 (1000)	39.4 (1000)		
	26	Length to face of forks	in (mm)	97 (2465)	100.5 (2555)		
	27	Wheelbase	in (mm)	68.9 (1750)	68.9 (1750)		
	28	Right angle stack	in (mm)	146.7 (3727)	149.3 (3793)		
	29	Equal aisle (90° intersecting aisle)	in (mm)	80.5 (2045)	81.7 (2074)		
	30	Outside turning radius	in (mm)	81.6 (2073)	84.2 (2139)		
	WT.	31	Truck weight (without battery - no load)	lb (kg)	8680 (3945)	9540 (4340)	
		32	Axle loading - drive - static with max weight battery (NL / RL)	lb (kg)	4855 (2205) / 13270 (6020)	5645 (2566) / 15150 (6886)	
		33	Axle loading - steer - static with max weight battery (NL / RL)	lb (kg)	4680 (2125) / 1765 (800)	5630 (2559) / 2125 (966)	
PERFORMANCE				Standard performance	PowerPlus performance	Standard performance	PowerPlus performance
	34	Travel speed (NL / RL)	mph (kph)	11.2 / 11.2 (18 / 18)	13 / 13 (21 / 21)	11.2 / 10.6 (18 / 17)	13 / 12.1 (21 / 19.5)
	35	Lift speed	Std 2 stg LFL mast (NL / RL) ft/min (m/sec)	124 / 75 (0.63 / 0.38)	142 / 96 (0.72 / 0.49)	116 / 65 (0.59 / 0.33)	124 / 83 (0.63 / 0.42)
			Opt 2 stg FFL mast (NL / RL) ft/min (m/sec)	124 / 77 (0.63 / 0.39)	130 / 93 (0.66 / 0.47)	108 / 65 (0.55 / 0.33)	116 / 81 (0.59 / 0.41)
			Opt 3 stg FFL mast (NL / RL) ft/min (m/sec)	124 / 77 (0.63 / 0.39)	134 / 94 (0.68 / 0.48)	112 / 65 (0.57 / 0.33)	118 / 81 (0.60 / 0.41)
	36	Lower speed	Std 2 stg LFL mast (NL / RL) ft/min (m/sec)	100 / 112 (0.51 / 0.57)		91 / 110 (0.46 / 0.56)	
			Opt 2 stg FFL mast (NL / RL) ft/min (m/sec)	91 / 106 (0.46 / 0.54)		73 / 102 (0.37 / 0.52)	
			Opt 3 stg FFL mast (NL / RL) ft/min (m/sec)	93 / 108 (0.47 / 0.55)		79 / 104 (0.40 / 0.53)	
	37	Gradeability	5 minute rating (NL / RL) %	35 / 24	38 / 26	34 / 22	37 / 24
			60 minute rating (NL / RL) %	12 / 8	13 / 9	11 / 7	12 / 8
	38	Drawbar pull	5 minute rating (NL / RL) lbf	4248 / 4148	4588 / 4480	4146 / 4037	4477 / 4360
			60 minute rating (NL / RL) lbf	1287 / 1257	1390 / 1357	1256 / 1226	1357 / 1321
ELECTRIC	39	Brake	Method of control (service / parking) Method of operation (service / parking)	Hydraulic / mechanical Foot / automatic	Hydraulic / mechanical Foot / automatic		
	40	Battery compartment type		Lithium-ion	Lithium-ion		
		Battery voltage (nominal capacity)	V/ah	83 / 360	83 / 360		
	41	Traction motors (dual) 60 minute rating (each)	hp (kW)	13.4 (10)	13.4 (10)	13.4 (10)	13.4 (10)
	42	Pump motor - 15 minute rating	hp (kW)	21.5 (16)	32.2 (24)	21.5 (16)	32.2 (24)
	43	Traction motors (type / control method)		Dual AC / transistor	Dual AC / transistor		
	44	Pump motor (type / control method)		AC / transistor	AC / transistor		
	45	Number of speeds (traction / pump)		Infinitely variable / Infinitely variable	Infinitely variable / Infinitely variable		
OTHER	46	Step height	in (mm)	18.7 (475)	18.7 (475)		
	47	Floor height	in (mm)	24.4 (620)	24.4 (620)		
	48	Attachment relief pressure	psi (bar)	2250 (155)	2250 (155)		
	49	Auxiliary oil flow (3rd and 4th function)	gal/min (l/min)	11 (40)	11 (40)		
	50	Sound level (measure per ANSI B56.11.5)	dB	63	65	63	65

The following chargers are approved to use with the J60XNL lithium-ion battery:

Posicharge ProCORE (80V) – 10kW, 15kW, 20kW, or 30kW single cable

EcoTec Fast Charge Access (80V) – 80-500-32FC or 80-650-32FC

Above specifications, unless otherwise listed, are for a standard truck without optional equipment. Right angle stack and equal intersecting aisle are calculated using a 40" wide pallet.

CERTIFICATION: Hyster lift trucks meet the design and construction requirements of B56.1-1969, per OSHA Section 1910.178(a)(2), and also comply with the B56.1 revision in effect at time of manufacture. Certification of compliance with the applicable ANSI standards appears on the lift truck. Performance specifications are for a truck equipped as described under Standard Equipment on this Technical Guide. Performance specifications are affected by the condition of the vehicle and how it is equipped, as well as by the nature, condition of the operating area, proper service and maintenance of the vehicle. If these specifications are critical, the proposed application should be discussed with your dealer.

STANDARD EQUIPMENT

30kW lithium ion battery
2-stage limited free lift (LFL) Vista™ mast with maximum fork height of 126" (3209mm)
5° forward and 5° back mast tilt
42" (1067mm) wide class III hook-type carriage with 48" (1219mm) high load backrest extension
42" (1067mm) long forks
Pneumatic drive tire and steer tire
Wheelbase – 68.9"
80-volt electrical system
Standard performance
Standard construction
Dual drive motors
Oil-cooled wet disc brakes
12" steering wheel with integral spinner knob
Non-suspension vinyl seat
Black ELR non-cinch seat belt
Automatic park brake
Key switch start
86.3" grid style overhead guard
MONOTROL™
3-function hydraulic control valve with TouchPoint hydraulic mini-levers with fully adjustable armrest
AC traction and pump motors (completely brushless)
Transistor drive and pump control
Advanced VSM (vehicle system manager)
Progressive thermal management system
Fully integrated CANbus communication
On-demand power steering
Hyster Stability System (HSS™)
Power assist braking
ADS (auto deceleration system) with regenerative braking
"Zero turn" steer axle
Multifunction display

- Battery state of charge with low battery lift interrupt
- Hour meter
- Performance mode indicator
- Fault indicator (audible & visible)
- 4 operator selectable, programmable performance modes

Low step height
Contoured handhold for entry / exit
Operator convenience station - storage areas, beverage & clipboard holders
Adjustable tilt steering column with low profile cowl
Operator presence system (OPS)
Anti-cinch operator restraint system
Cushioned floor mat
Static strap
Tow pin
Seatside power disconnect button
On-board software (program, test & diagnose; password protected)
Electronic horn with integral relay (long life / no adjustments)
24 month / 4,000 hour powertrain warranty
12 month / 2,000 hour full truck warranty
84 month / 12,000 hour lithium-ion battery warranty
Operating manual


OPTIONAL EQUIPMENT

PowerPlus performance
Available with 2-stage limited free lift (LFL) and 2- or 3-stage full free lift (FFL) Vista™ masts
Carriage with integral sideshift
Carriage with integral sideshifting fork positioner
Mast tilt option – 10° forward / 5° back
Mast tilt option – 5° forward / 6° back
Return to set tilt
Accumulator
4-function hydraulic control valve
Solid pneumatic tires
Wide tread tires
Non-suspension seat (cloth)
Full suspension seat (vinyl or cloth)
Air-ride suspension seat (vinyl or cloth)
Swivel seat, full suspension (vinyl or cloth)
Front and top cab panels: includes front panel with wiper / washer and top panel
Keyless start (with auxiliary key switch)
Seat side directional control
Telescopic steering column with tilt memory
LED and halogen work light packages
LED dome / reading light
LED brake / tail / back-up light packages
Audible reverse activated alarm
Visible amber strobe light - continuous activated, overhead guard mounted
Rear drive handle with integrated horn button
Mirrors – side view or panoramic
Load weight indicator
Impact monitor
Operator password
Operator daily checklist
System monitor – hydraulic low fluid level indicator and hydraulic filter service indicator
Hydraulic attachment extension tubes with or without quick disconnect fittings
Fire extinguisher – 2.5 lb. dry chemical
Synchronous steering
Red (HI-VIS) ELR (emergency locking retractor) non-cinch seat belt
Red (HI-VIS) ELR (emergency locking retractor) non-cinch seat belt with start interlock
Low mount display
IP54 sealed drive axle/motors with belly pan and side shields
Outdoor protection / wash-down package
Front mud guards
Tilt cylinder boots



Hyster Company
P.O. Box 7006
Greenville, North Carolina
27835-7006
Part No. J50-60XNL/TG
4/2020 Litho in U.S.A.

Visit us online at www.hyster.com or call us at 1-800-HYSTER-1.

Hyster, , and STRONG PARTNERS. TOUGH TRUCKS. and MONOTROL are registered trademarks in the United States and certain other jurisdictions. Hyster products are subject to change without notice.

Trucks may be shown with optional equipment. © 2020 Hyster Company. All rights reserved.

HYSTER® J50-60XNL

POWERED BY LITHIUM-ION TECHNOLOGY



Introducing the Hyster® J50-60XNL sit-down counterbalanced forklift powered by integrated lithium-ion technology—a power solution built for both indoor and outdoor applications that demand high efficiency, charging flexibility, zero maintenance and smart sustainability.

The J50-60XNL embraces technology that focuses on advancing your operation and the material handling industry which makes it a powerful addition to the Hyster full line of lift trucks.



WHY LITHIUM-ION?

**ZERO MAINTENANCE:
NO MORE ...**



- Watering
- Acid
- Spills
- Fumes
- Cleaning
- Equalizing

**LESS THAN
1 HR**



FULL CHARGE TIME
WITH 30kW POSICHARGE® PROCORE

up to **18%** 
MORE EFFICIENT
THAN J50-60XN WITH LEAD ACID*

FDA COMPLIANT
ZERO EMISSIONS TECHNOLOGY
WITH NO GASSING

The J50-60XNL is at the forefront of innovation and leading the way for a counterbalanced lift truck engineered around a fully integrated, space-saving, lithium-ion battery. The strategic design helps free space in the operator compartment maximizing comfort and convenience to help propel productivity.

1 REDUCED TRUCK WEIGHT

- Improves acceleration
- Reduces energy consumption during long runs in demanding applications

2 REPOSITIONED CENTER OF GRAVITY

- Enhances drive quality
- Improves truck handling in corners

3 LOWERED SEAT AND FLOOR PLATE

- Allows easy entry and exit from the truck

4 OPEN SPACE DESIGN

- Maximizes comfort and convenience
- Allows easy entry and exit from the truck
- Gives increased freedom to position feet during operation

5 ENERGY EFFICIENT

- Fast charging times - less than 1 hour full charge time.**
- Truck retains full suite of low state of charge safety features
- Battery warranty - 7 years/12,000 hours
- Truck requires either a PosiCharge ProCore or Ecotec Fast Charge Access


6 INCREASED HEAD ROOM

- Best in class head room allows increased ergonomics for taller operators.
- Extra space allows the option for Air-Ride Seats for a smoother ride and operator comfort.



		J50XN (Lead Acid)	J50XNL (Integrated Lithium-ion)	J60XN (Lead Acid)	J60XNL (Integrated Lithium-ion)
Truck weight with min battery	lb	11020	9540	11180	10400
Seat index point from ground - full suspension	in	46.2	42.8	46.2	42.8
Headroom - seat index point to bottom of OHG	in	39.0	42.4	39.0	42.4
Length to face of forks standard carriage	in	97	97	98.1	100.7
Aisle width for pallets 48" long x 40" wide - no clearance	in	146.7	146.7	147.8	150.4
Outside turning radius	in	81.6	81.6	81.6	84.2
Step height from ground to floor	in	27.8	24.4	27.8	24.4



Hyster,  and STRONG PARTNERS. TOUGH TRUCKS. are registered trademarks in the United States and certain other jurisdictions. Hyster products are subject to change without notice. Trucks may be shown with optional equipment.
© 2020 Hyster Company. All rights reserved. 6/2020

* High Performance Motors - Extended Shift Off - 60% Regen braking

** Requires 30kW PosiCharge ProCore